

Level Best 433 Extra Heavy Commercial Traffic



433 098
Get Even



433 009
Level Headed



433 091
Created Equal



433 010
Smooth Move



433 096
Nothing Flat



433 094
Level With Me

Size
7.25" x 48" nominal (18.5 cm x 122 cm)
5 mm thick

Wear Layer
28 mil / UV-Cured Urethane
MCX™ MicroCeramic Reinforced Resin

Embossing
Real Touch™ Embossed in Register

Edge Treatment
Four-Sided Microbevel

Installation
Full Spread Adhesive
Recommended Adhesive: NEXT 1200™

Coordinating Moldings
See nextfloor.net for more details.

Packaging
9 pieces per carton (44 lbs)
21.8 SF per carton
50 cartons per pallet
20 pallets per container

Testing

Critical Radiant Flux	ASTM E648	Class I
Surface Flammability	DOC FF 1-70	Passed
Coefficient of Friction	ASTM 204	Passes>0.6
Static Load Limit	ASTM F970	1200 lbs
Sound Transmission Class (STC)	ASTM E492	62
Impact Insulation Class (IIC)	ASTM E989	57
High Frequency Impact Insulation Class(HIIC)	ASTM E3222	89
Floor Score Certified		
Phthalate Free		
100% Virgin PVC		



Warranties
Lifetime Waterproof
Lifetime Residential Wear
40-Year Commercial Wear
Lifetime Transition Integrity*
*When installed beside Next Floor nylon carpet tile.
See full warranty text at nextfloor.net

Sample SKUs

Handle Boards
HB433NF
**includes Bandwidth Carpet
10 per carton (110 lbs)*

Strap Sets
SS433NF
5 per carton (36 lbs)

Folders
2P433NF
**includes Bandwidth Carpet
20 per carton (60 lbs)*

Extra Heavy Duty LVT

- 5 mm total thickness
- 28 mil wear layer
- MCX™ MicroCeramic protection
- 40-Year Commercial Warranty

